



# Shenyang Sharjah Bearing Co.,Ltd.



FYR 2.11/16 H Bearing 2D drawings and 3D CAD models

## SKF FYR 2.11/16 H Flange Block Bearings

Bearing No. FYR 2.11/16 H

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	12.26
EAN	7316576664168
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22215
Seals	Trigard
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Round Flange Block; 2-11/16" Bore; 7.9" Bolt Circle; 5.6" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Spherical Roller Bearing; 3-5/8" Length Thru Bore;
Other Features	Double Row   Heavy Duty



## Shenyang Sharjah Bearing Co.,Ltd.

	Open End   With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	FYR 2.11/16 H
Weight / LBS	27
Cartridge Pilot Depth	0 Inch   0 Millimeter
Bolt Spacing	5.6 Inch   141.4 Millimeter
Nominal Bolt Circle Diameter Round	7.9 Inch   200 Millimeter
d	2.688 Inch   68.275 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
D	3.625 Inch   92.075 Millimeter
bore diameter:	2-11/16 in
locking device:	Set Screw
bolt center-to-center length:	7.8750 in
expansion type:	Non-Expansion Bearing (Fixed)
bolt circle diameter:	7-7/8 in
seal type:	Contact/Lip
overall length/diameter:	9.2500 in
overall depth:	3-7/8 in
flange mounting type:	Four-Bolt Round
radial dynamic load capacity:	35500 lb
bearing type:	Spherical Roller
radial static load capacity:	46800 lb
housing construction:	Solid Flange Mount
operating temperature	Maximum of +110 ° F ° F



## Shenyang Sharjah Bearing Co.,Ltd.

range:	
bore type:	Round
finish/coating:	Uncoated
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	222